

Tire Pressure Monitoring System

Availability: Pre-Order

Price: \$499TTD



Short Description

4 TPMS Sensors (0-6 Bar / 0-87 PSI)

Description

Product details

Brand

Tymate

- ? Full-Color Screen Design ? Tymate Tire Pressure Monitoring System CL205 provides a stylish, high-end appearance, which enhances the sense of technology and the grade of the environment in the car. This tpms is small-size and light-weight, saving space. Its screen displays the tire pressure and temperature in real-time and provides visual and audible alarms when abnormal conditions occur.
- ? Six Types Of Alarms And User-set Alarm Values ? Tymate Tire Pressure

Monitoring System CL205 provides six-alarm modes (including fast leak alarm, high/low-pressure alarm, high-temperature alarm, sensor low voltage alarm, and sensor fault alarm). You can set the pressure and temperature alarm values in your free. (TP setting range: 12-87 PSI. Two units of tire pressure Bar/PSI and one unit of temperature ?)

- ? Car Cigarette Lighter Charging Method ? Tymate Tire Pressure Monitoring System CL205's charging method is very convenient, preventing from worrying about being lost due to small size, and maintaining the state of long-term power. It will also display the voltage of the battery in the car to help you know if there is any abnormality in the car battery. (Please keep the power on during use, otherwise, the system may go to automatically restore factory settings after power off)
- ? Low Power Consumption And Long Working-life Sensor ? Tymate Tire Pressure Monitoring System CL205 equipped with 4 advanced external sensors, which are low power consumption (a CR1232 battery can be used for half a year) and have long working life (can reach 2 years maximum). Small size, light-weight, high accuracy of sensing tire pressure [small acceptable tire pressure error (?3psi)], and easy installation, it also can withstand harsh environments. (0-6 Bar/ 0-87 PSI)
- ? Installation Methods ? The sensors are all programmed before leaving the factory, so you don't need to pair them manually. After receiving the goods, please power on the display first, and then install the sensors one by one. Then start the car for 5-10 minutes to activate the sensor.

Legal Disclaimer

Note Before Purchase

How Can I Know If This Device Can Fit My Vehicle?

You should first figure out the following points to determine whether your vehicle can use this device:

1. The number of tires of your vehicle: 4 tires or 6 tires? We do not recommend you to use these models on the RV trailers or other large

vehicles: CL205, M12-3 Black, TM527M, M7-3.

If the type of your vehicle is RV or trailer, please consider the model: M12-3 Blue.

2. the body length of your vehicle: What is the length of your vehicle? If you have purchased a Tymate product that does not fit a repeater, please make sure that your vehicle is less than 30ft in length (consider the interference of objects and electromagnetic). If you have purchased a product that adapts to the repeater (M12-3 Blue), then you do not need to worry about whether the length of the vehicle can be matched. Because the maximum signal transmission distance can reach 40ft (consider the interference of objects and electromagnetic).

3. Standard tire pressure value: You can check the standard tire pressure value of your own tire. Under normal circumstances, the tire manufacturer will print this standard tire pressure value on the tire body, or on the "Tire Manual". If you have original tires that fit the vehicle, you can also see this recommendation on the left side of the main driving position.

Note: If your standard tire pressure value exceeds the maximum tire pressure value that can be detected by this tpms (87PSI), or when your tire is in a hot tire state, it will exceed 87PSI, we sincerely advise you consider other models.

4. The need to set the alarm value: **Please note before buying that the range of the lowest and highest tire pressure values that this product can set is 12-87PSI. If your demand for monitoring tire pressure alarm values exceeds this range, we suggest you consider other models.**

Why Is Not Date Displayed After I Installed It?

After the first installation, all data will be displayed after driving for 5-10 minutes. The sensor needs motion activation.

THE Measurement error

The error value of measuring tire pressure is ± 3 PSI.

The Sensor Or Monitor Is Not In The Normal Operation

If you encounter any other problems, please do not hesitate to contact us!

Product Gallery

MULTIPLE MONITORING MODES



COMES WITH 5V/2.4A USB CHARGING OUTPUT



Comes with 5V/2.4A USB charging output



APPLICABLE TYPES OF VEHICLE

Suitable for SUV, MPV, COUPE, VAN, COACH
(Universal Tire Pressure 22-87PSI, 1.5-6BAR)



Tymate

Tymate Tire Pressure Monitoring System
Accurate measurement of your tire pressures, keeping your driving safe.

An advertisement for the Tymate Tire Pressure Monitoring System. It features a white SUV on a sandy dune under a blue sky. In the foreground, there are several black tires and a black rectangular device with a digital display showing '35 PSI' and '28 PSI'. The text 'Tymate' is in a blue box, and the product name and description are in black.

Widely used in most types of 4-wheel vehicle
Such as SUV, VAN, COACH, Minibus, (3 to 8/9/12 /13 to 60seater)

An advertisement showing a variety of vehicles. In the center, a white van is shown from a side profile. Surrounding it are several smaller images of different cars and SUVs in various colors (red, blue, yellow, black). The text 'Widely used in most types of 4-wheel vehicle' is in bold, and the list of vehicle types is in a smaller font below it.